

SPANN-BOX® SIZE 30

Three tension pressure settings

Spann-Box® size 30 provides high quality at the same time as being economically priced. The robust plastic housing gives high resistance to corrosion.

		Light	Heavy
Tension force	1 released spring	58 – 32 N	132 – 60 N
	2 released springs	116 – 64 N	264 – 120 N
	3 released springs	174 – 96 N	396 – 180 N
	Tension distance	40 mm	40 mm

SPANN-BOX® SIZE 30 with arc segment profile

Stainless steel screws and springs



Applications

- Environments with a risk of corrosion
- No high mechanical stresses

Tensioning pressure

- Choice of light or heavy spring force

Attachment

- Installed underneath the chain
- Bore holes in the housing (for matching fastening brackets refer to pages 118 - 119)

DIN 8187 chain no.	B mm	Light tension force Article no.	Heavy tension force Article no.
≤06B-1 (U-Profile)	20	281 030 001	281 030 002
08B-1	20	281 030 003	281 030 004
10B-1	20	281 030 005	281 030 006
12B-1	20	281 030 007	281 030 008
16B-1	20	281 030 009	281 030 010
05B-2	20	281 030 011	281 030 012
06B-2	20	281 030 013	281 030 014
08B-2	20	281 030 015	281 030 016
10B-2	25	281 030 017	281 030 018
12B-2	30	281 030 019	281 030 020
05B-3	20	281 030 021	281 030 022
06B-3	25	281 030 023	281 030 024
08B-3	30	281 030 025	281 030 026
10B-3	40	281 030 027	281 030 028
12B-3	45	281 030 029	281 030 030

Special designs on request

