

DG4V 5 6C M U C6 20, DG4V56CMUC620, DG4V56CMUC620

Product specifications

Characteristic	Value
Actuation type	Solenoid operated
Brand	Vickers by Danfoss
Coil Rating	220 VAC 50Hz
Design series	20 Series
Electrical Connection	ISO 4400 (Din 43650) connector
Energ Time	30-40 ms
Flow rate upto GPM	32.0
Flow rate upto LPM	120.0
Fluid Compatibility	Petroleum oils
Fluid cleanliness	19/17/14 micron
Indicator light	No
Interface	ISO4401-05/NFPA D05
Manual override	Plain
Model Code	DG4V56CMUC620
Model Code 1	DG4V56CMUC620
Performance	High performance
Power Consumption	105 VA
Pressure rating BAR	315
Pressure rating PSI	4500
Seal type	Viton
Solenoid Energising ID	Standard as per ANSI B93 9

Characteristic	Value
Special features	None
Spool Position Monitor	No
Spool Type	Spool 6
Spring arrangement	Spring centred
Stage	Single stage
Surge Suppr Damper	No
Tank port rating BAR	120
Tank port rating PSI	1750
Valve mount type	Subplate/manifold mounted
Valve type	Directional control valve
Working temp max C	50
Working temp max F	122
Working temp min C	-20
Working temp min F	-4