

R3 Retracta Spring Rewind Hose Reels

In the toughest environments across the world, the original Retractable polypropylene reel has built an enviable reputation for dependability. Building on this and with Macnaught's long history of innovation and design, they have developed the exciting new Retracta R3. Engineered to create an even higher industry benchmark, the Retracta R3 has created new levels of efficiency and dependability into a new era. At the heart of this innovation is the patented RACR 'Retractable Adjustable Control Return' system, which can be supplied with or retro fitted to any R3 Retracta. This world first control return system offers true control by allowing the user to set the speed of return to suit their individual requirements.

The RACR system is fully serviceable and carries the same 10 year warranty and parts guarantee found with the entire Retracta family.

FEATURES:

- Tough, corrosion free polypropylene construction
- Supplied with fitted hose for specified application
- New high-wear resistant mouth design
- Increased internal capacity
- Overrun protection on spring
- Upgraded main spring (internal)
- Safe tensioning mechanism
- Fully serviceable – all parts readily available
- Optional RACR 'Retractable Adjustable Control Return' for all R3 models
- Fully warranted



All Retracta models (on BU100 bracket)			
Reel dimensions			Approx weight with hose
W	H	D	
225mm	474mm	621mm	13kg / 29lb

Application	Model	Hose length	Hose size (I.D.)	Hose type	Working pressure	Inlet size	Hose outlet	Reel colour
Compressed air	AR320R	20m (66')	3/8" (10mm)	Rubberised reinforced PVC	250psi (17bar)	3/8" BSPF	1/4" BSPM	Red
Compressed air	AR415R	15m (50')	1/2" (12.5mm)	Rubberised reinforced PVC	250psi (17bar)	3/8" BSPF	3/8" BSPM	Red
Cold wash 40°C	CW415B	15m (50')	1/2" (12.5mm)	Reinforced PVC	150psi (10 bar)	3/8" BSPF	1/2" BSPM	Blue
Hot wash 90°C	HW415R	12m (40')	1/2" (12.5mm)	HT chem resistant PVC	150psi (10 bar)	3/8" BSPF	1/2" BSPM	Red
Diesel Delivery	HD200B3	12m (40')	1/2" (12.5mm)	Diesel Hose	150psi (10 bar)	1/2" BSPF	1/2" BSPM	Blue
Propane	HP100R3	15m (50')	3/8" (10mm)	Propane Hose	150psi (10 bar)	3/8" BSPF	3/8" BSPM	Red
Food Quality Water 92°C	HFQ200R3	12m (40')	1/2" (12.5mm)	FDA Hose	150psi (10 bar)	1/2" BSPF	1/2" BSPM	Red
High pressure water 95°C	WHP100R3	20m (66')	3/8" (10mm)	Wire reinforced rubber	3000psi (205 bar)	3/8" BSPF	3/8" BSPM	Red
Chemical	WP100R3	16m (52')	3/8" (10mm)	Chemical resistant PVC	250psi (17bar)	3/8" BSPF	1/4" BSPM	Red
Oxy-acetylene	HOA200B3	15m (50')	3/8" (10mm)	Dual hose reinforced rubber	175psi (12bar)	Gas thread	Gas thread	Blue
Oxy-acetylene	HOA100B3	15m (50')	1/4" (6mm)	Dual hose reinforced rubber	175psi (12bar)	Gas thread	Gas thread	Blue
Oxy-propane	HOP200B3	15m (50')	3/8" (10mm)	Dual hose reinforced rubber	175psi (12bar)	Gas thread	Gas thread	Blue
Oxy-propane	HOP100B3	15m (50')	1/4" (6mm)	Dual hose reinforced rubber	175psi (12bar)	Gas thread	Gas thread	Blue
Oil medium pressure	OMP400B3	15m (50')	1/2" (12.5mm)	Wire reinforced rubber	1000psi (69 bar)	1/2" BSPF	1/2" BSPM	Blue
Grease	GR210B	10m (30')	1/4" (6mm)	Wire reinforced rubber	5000psi (340 bar)	1/4" BSPF	1/4" BSPM	Blue
Garden reel	DR418G	18m (60')	1/2" (12.5mm)	PVC	100psi (7 bar)	3/4" Male	Blank/Nozzle	Green
Breathing Air	BH100R3	15m (50')	3/8" (10mm)	Black Anti-static NBR/PVC	175psi (12 bar)	3/8" BSPF	3/8" BSPM	Red
Breathing Air	BH100R3-RESP	15m (50')	3/8" (10mm)	Yellow Respirax	150psi (10bar)	3/8" BSPF	3/8" BSPM	Red

All reels supplied with BU100 bracket for wall mounting to 1.8 mtr and overhead. For higher wall or bench/floor mounting specify BB100 bracket when ordering. Additional mounting brackets are available.

RETRACTA[®] R3

by macnaught

