


Media: air
 Inlet Pressure: 30 bar max
 Pressure range: 0.5 – 30 Bar
 Media temp: -10°C - +70°C
 Ambient temp: -10°C to +70°C
 Mounting: any position
 Weight: 2000g



Stainless Filter/Regulator

3/8 – 1/2

316 Stainless Steel

Manual – Semi – Full Auto Drain

0.5 – 30 Bar

TYPE USFR02-03-04



PRESSURE

Ø Port BSP	Max Flow Air L/min @ 6Bar (ANR)	Pressure (Bar)		Part Number
		Min	Max	
1/4	2200	0.5	12	USFRB02
3/8	2500	0.5	12	USFRB03
1/2	3800	0.5	12	USFRB04
1/4	2200	12	30	USFR02
3/8	2500	12	30	USFR03
1/2	3800	12	30	USFR04

OPTIONS

5 Micron Filter Element
 Semi-Automatic drain
 Mounting Bracket and Screws
 Pressure Gauge and Blanking Plug
 Fully Automatic Drain (D)
 40 Micron Filter Element
 NPT Thread

CONSTRUCTION

Body, Filter Bowl (110cc), Regulator, 5 or 40 micron Filter Elements, Mounting Bracket, Blanking Plug: 316 Stainless Steel
 Pressure gauge: Case 304 stainless steel / thread 316 Stainless Steel
 Test Pressure: 60 Bar

OVERALL DIMENSIONS

